



Great Lakes' Fan Assembly Specifications

	Assembly Information							
	CFM	AMP	VAC	Hz	dBA (High End)	# of Fan Motors	Fan Motor Part #	RMU
721704	75	0.2	115	50/60	39.0	1	XF01	N/A
7217-WS	150	0.4	115	50/60	42.0	2	XF01	N/A
7217	225	0.6	115	50/60	43.8	3	XF01	N/A
7217FT	225	0.6	115	50/60	43.8	3	XF01	2
7217FT-3	225	0.6	115	50/60	43.8	3	XF01	2
7217FT-6	450	1.2	115	50/60	46.8	6	XF01	2
7217FT-9	675	1.8	115	50/60	48.5	9	XF01	2
7217LE2	150	0.4	115	50/60	42.0	2	XF01	N/A
7217LE3	225	0.6	115	50/60	43.8	3	XF01	N/A
TPE-24F	225	0.6	115	50/60	43.8	3	XF01	N/A
TPE-29F	225	0.6	115	50/60	43.8	3	XF01	N/A
TPES-F	225	0.6	115	50/60	43.8	3	XF01	N/A
TPE-24F10	550	0.28	115	50/60	55.0	1	721710	N/A
TPE-29F10	550	0.28	115	50/60	55.0	1	721710	N/A
TPES-F10	550	0.28	115	50/60	55.0	1	721710	N/A
TPE-242F10	1100	0.56	115	50/60	58.0	2	721710	N/A
TPE-292F10	1100	0.56	115	50/60	58.0	2	721710	N/A
TPES-2F10	1100	0.56	115	50/60	58.0	2	721710	N/A

	Individual Fan Motor Information	
	XF01	721710
Dimensions (in)	4.7 x 4.7 x 1.5	Ø10.0 x 3.5
Bearing System	Ball Bearing	Dual Ball
Frame	Diecast Aluminum	Diecast Aluminum
Impeller	PBT, UL94V-O Plastic	PBT, UL94V-O Plastic
Motor	AC Shaded Pole, Impedance & Thermally Protected	Capacitor Drive, Impedance & Thermally Protected
Insulation Resistance	10M Ohm Between Leadwire & Frame (500VDC)	>100M Ohm Between Leadwire & Frame (500VDC)
Dielectric Strength	1 min at 1500 VAC, 50/60 Hz	1 min at 1500 VAC, 50/60 Hz
Life Expectancy (L10 @ 40C)	50,000 Hrs	60,000 Hrs
Nominal Voltage (VAC)	115	115
Voltage Range (VAC)	80-130	80-130
Rated Current (Max. Amp)	0.2	0.28
Rated Power (W)	9	35
Rated Speed (RPM)	2300	1650
Airflow (CFM)	75	550
Noise (dBA)	39	55
Max. Static Pressure (In. H2O)	0.16	0.39

Product specification and availability are subject to change without prior notice. GLCC is not responsible for typographical errors.