

2-1716219-3 | C-004-L2-5L-M04BK/40G/GY/FS/B

Fire Survival (120min) Fiber Optic Cable, multimode, OM3, 4-fiber, loose tube, gel filled, ULSZH, 2000 m. Provides Rodent Resistance.

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA
Portfolio	CommScope®
Product Type	Fiber indoor/outdoor cable
Product Series	C-L2

General Specifications

Armor Type	Corrugated steel
Cable Type	Loose tube
Subunit Type	Gel-filled
Jacket Color	Black
Jacket Marking	Meters
Jacket Marking Method	Inkjet
Jacket Marking Text	COMMSCOPE GB SYSTEM F.O. CABLE X-1716219-3 INT/EXT FIRE SURVIVAL 4x50/125 OM3 [Serial number] [metre mark]
Fibers per Subunit, quantity	4
Total Fiber Count	4

Dimensions

Diameter Over Jacket	12.7 mm 0.5 in
-----------------------------	------------------

Optical Specifications

Fiber Type	OM3, bend insensitive
-------------------	-----------------------

Optical Specifications, Wavelength Specific

Standards Compliance	TIA-492AAAD (OM4)
-----------------------------	-------------------

Environmental Specifications

EN50575 CPR Cable EuroClass Fire Performance	B2ca
EN50575 CPR Cable EuroClass Smoke Rating	s1b

2-1716219-3 | C-004-L2-5L-M04BK/40G/GY/FS/B

EN50575 CPR Cable EuroClass Droplets Rating	d0
EN50575 CPR Cable EuroClass Acidity Rating	a1
Environmental Space	Universal Low Smoke Zero Halogen (ULSZH)
Flame Test Listing	EN 50399 IEC 60332-1-2
Flame Test Method	EN 50399 IEC 60331-25 (120) Fire resistance: 120 minutes at 750 °C (no fiber break) IEC 60332-1-2 IEC 60754-2 IEC 61034-2

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

