

VGC™ AC Power Cords. 3 Wire



Features & Benefits

- Economical power cord capable of providing power to multiple devices
- Offered in multiple lengths to suit your specific application
- Lifetime warranty- durable construction for years of reliable trouble free service

Standards Compliance

- NEMA 5-15-P
- IEC-320-C13
- UL Listed
- RoHS Compliant

Construction

Conductor Type: 18 AWG, 3 conductor

Conductor Material: Stranded bare copper

Male Connector Type: NEMA 5-15-P

Female Connector Type: IEC-320-C13

Connector Finish: Nickel plated

Connector Housing Material: PVC

Connector Housing Color: Black

Jacket OD: 6 mm

Electrical

Connector Maximum AC Voltage: 125 Volts

Connector Maximum Amps: 10A

Connector Maximum Watts: 1250W

Cable Maximum AC Voltage: 300 Volts

Environmental Conditions

Operating Temperature: 221°F (105°C)

Cable Marking

(UL) c(UL) E365678 SJT 60°C 3X18AWG(0.824MM2)
300V VW-1 VERICOM

Applications

The Vericom AC power cord 3 conductor C13 is ideal for computers, printers, monitors, and other devices in a commercial or residential environment.

Description / Specifications

Designed with a female IEC-230-C13 and male NEMA 5-15-P connectors, these cables are perfect for most computers, printers, monitors and other devices. This power cable is constructed using three 18 AWG conductors and two molded connectors to ensure a solid connection. These cables are UL Listed and RoHS Compliant and are available in multiple lengths.

Ordering Information

Description	AC Power Cord 3 Conductor C13
Cord Length	Item Number
1 ft.	XPS01-00940
2 ft.	XPS02-00941
3 ft.	XPS03-00533
4 ft.	XPS04-00942
5 ft.	XPS05-00943
6 ft.	XPS06-00534
9 ft.	XPS09-00535
12 ft.	XPS12-00536
25 ft.	XPS25-03447
50 ft.	XPS50-03432